



NOTES

1. ANY RAINWATER HARVESTING SYSTEM REQUIREMENTS TO BE DESIGNED BY OTHERS. LAYOUT SHOWN DOES NOT INCLUDE SUCH PROVISION.
2. SURFACE WATER INLET HEADWALL TO HAVE BAFFLE TO DISSIPATE WATER VELOCITY. SCREEN TO BE PROVIDED TO PREVENT ACCESS
3. ALL DRAINAGE WORKS SHALL BE CARRIED OUT IN ACCORDANCE WITH BUILDING REGULATIONS 2002 EDITION, CEWM AND SEWERS FOR ADOPTION 6TH EDITION AND THE SPECIFICATION FOR HIGHWAY WORKS.
4. INSITU AND PRECAST CONCRETE UNITS SHALL HAVE SULPHATE RESISTING PORTLAND CEMENT TO BS 4027 UNLESS AGREED OTHERWISE.
5. PRECAST CONCRETE PRODUCTS SHALL COMPLY WITH RELEVANT PROVISIONS OF BS 5911 AND BE KITEMARKED. PIPES TO BE STRENGTH CLASS IN ACCORDANCE WITH BS EN1295-1:1998.
6. GULLY GRATES AND FRAMES SHALL COMPLY WITH THE RELEVANT PROVISIONS OF BS EN124.

KEY

- FOUL WATER GRAVITY DRAINAGE AND MANHOLE
- FOUL WATER RISING MAIN AND PUMP STATION
- SURFACE WATER GRAVITY DRAINAGE AND MANHOLE
- SURFACE WATER RISING MAIN AND PUMP STATION.
- PRE TREATMENT PROCESS EFFLUENT GRAVITY DRAINAGE
- PRE TREATMENT PROCESS EFFLUENT RISING MAIN AND PUMP STATION
- CELLULAR ATTENUATION TANK
- ACO DRAINS
- HEADWALL. HEADWALLS 1 AND 2 INLETS, HEADWALL 3 OUTLET
- PLANNING BOUNDARY
- RAINWATER HARVESTING SYSTEM AND MANHOLE